

# EMF rozsah

Profil	Šířka [mm]	Počet pinů	Max. pracovní napětí	Carbonový pin
T 5	10	5	96	
	16	5	144	
		8	224	
		5	176	
	20	8	232	
		5	176	
		8	256	
	32	5	304	
		8	450	
		5	360	
	50	8	480	
		4	216	
8		320		
T 10	16	12	640	
		4	240	
		4	304	•
	25	8	504	•
		11	680	•
		4	400	•
	32	8	576	•
		12	880	•
		4	624	•
	50	8	1120	•
		11	1480	•
		4	800	
	75	8	1600	
		11	1760	
		4	1040	
	100	8	2000	
		11	2280	
		4	1600	
T 20	25	4	536	
		11	1600	
		4	784	
	32	6	1200	
		4	960	
		11	3040	
75	4	1600		
	11	3560		
	4	2130		
100	11	7600		
	4	256		
	8	500		
AT 5	16	12	960	
		4	344	
		4	384	•
	25	8	624	•
		11	904	•
		4	640	•
	32	8	800	•
		12	1200	•
		4	880	•
	50	8	1680	•
		11	2160	•
		4	1040	
AT 10	75	8	2320	
		11	2640	
		4	1440	
	100	8	2720	
		11	3440	
		4	1600	

Profil	Šířka [mm]	Počet pinů	Max. pracovní napětí	Carbonový pin	
AT 20	25	4	800		
		11	1760		
		4	1200		
	32	6	1520		
		4	1600		
		11	4400		
	50	4	1920		
		11	6080		
		4	2700		
	100	11	7700		
		10	5	120	
		15	5	168	
HT 5	20	8	240		
		5	224		
		8	296		
	25	5	280	•	
		8	376	•	
		5	320	•	
	32	8	510	•	
		5	480	•	
		8	640	•	
	50	4	728	•	
		8	1096	•	
		5	800		
100	8	1520			
	15	5	256		
	5	360			
HT 8	20	5	376	•	
		10	784	•	
		5	784	•	
	25	14	960	•	
		5	400		
		11	960		
	30	5	800	•	
		10	1440	•	
		14	2080	•	
	50	22	2300	•	
		5	1320		
		10	2400		
75	14	2880			
	9	2320			
	5	1760			
85	10	3200			
	14	3600			
	5	1600			
100	10	3200			
	14	3600			
	5	1600			
HT 14	40	5	1120		
	55	5	1600		
	85	5	2400		

Profil	Šířka [mm]	Počet pinů	Max. pracovní napětí	Carbonový pin	
RP 5	10	5	120		
		5	168		
		8	240		
	15	5	224		
		8	296		
		5	280	•	
	20	8	376	•	
		5	320	•	
		8	510	•	
	25	5	480	•	
		8	640	•	
		4	728	•	
32	8	1096	•		
	5	800			
	8	1520			
RP 8	50	15	5	256	
		20	5	360	
		5	376	•	
	25	10	784	•	
		14	960	•	
		5	400		
	30	11	960		
		5	800	•	
		10	1440	•	
	50	14	2080	•	
		22	2300	•	
		5	1320		
75	10	2400			
	14	2880			
	9	2320			
85	5	1760			
	10	3200			
	14	3600			
RP 14	40	5	1120		
	55	5	1600		
	85	5	2400		

Profil	Šířka [mm]	Počet pinů	Max. pracovní napětí	Carbonový pin	
ST 5	10	5	120		
		5	168		
		8	240		
	15	5	224		
		8	296		
		5	280	•	
	20	8	376	•	
		5	320	•	
		8	510	•	
	25	5	480	•	
		8	640	•	
		4	728	•	
32	8	1096	•		
	5	800			
	8	1520			
ST 8	75	15	5	256	
		20	5	360	
		5	376	•	
	25	10	784	•	
		14	960	•	
		5	400		
	30	11	960		
		5	800	•	
		10	1440	•	
	50	14	2080	•	
		22	2300	•	
		5	1320		
75	10	2400			
	14	2880			
	9	2320			
85	5	1760			
	10	3200			
	14	3600			
ST 14	40	5	1120		
	55	5	1600		
	85	5	2400		
L	12,7	4	144		
	19,05	5	256		
	25,4	5	288	•	
	38,1	5	480		
	50,8	5	560	•	
	78,2	5	1000		
H	101,6	5	1200		
	12,7	4	160		
	19,05	4	240		
	25,4	4	304	•	
	38,1	4	520		
	50,8	4	640	•	
HX	78,2	4	880		
	101,6	4	1120		
	50,8	10	3060		

